

Tyre Shines

Detailing Products for all Industry Types



Non Silicon



Tyre Gloss

Tyre Gloss is a silicone free tyre shine designed for use in the panel repair industry, where the use of silicone products is prohibited. Although the longevity of a tyre shine is less than with silicon formulations, Tyre Gloss offers very good coverage, and presentation, with reasonable longevity. Typically one can expect the product to stand up to 2 to 5 days in most climatic conditions.

- Fast Drying
- Silicon Free
- Non Regulated (non flammable)

Silicon Tyre Shines



All Shine 2

Sierra's premium Tyre Shine. All Shine 2 is designed to give the absolute best finish, with minimal coverage, and produce an outstanding shine. The shine level achieved with Sierra's All Shine 2 is a high gloss or 'wet look' appearance. Durability is excellent, with expected periods of one to two weeks being typical. All Shine 2 is highly recommended for use in auction houses and prestige dealerships. There is no better tyre shine.

- Very Fast Drying
- High Gloss Finish
- Durable
- Regulated – Class 3



All Shine 1

Superb durability, and the most widely used amongst professionals requiring a good quality tyre shine at an affordable price. Produces a 'new tyre' look or satin finish which will last for at least a week in most climatic conditions. Excellent coverage and flashes dry in minutes, allowing the vehicle to be driven almost immediately after application. All Shine 1 is recommended for use by most professional detailers – dealerships, and mobile detailing.

- Very Fast Drying
- Satin Finish
- Durable
- Regulated – Class 3



Tyre Slick

Budget Tyre Shine. Tyre Slick is designed to give a satin finish, that produces a new tyre look. The durability is excellent, with expected periods of one week being typical. Tyre Slick is highly recommended for use in used car yards as well as dealerships.

- Very Fast Drying
- Satin Finish
- Durable
- Regulated – Class 3



Armourshield

Armourshield may be utilized as a tyre shine in applications where a silicon product is preferred for the sake of durability, but workplace practices prohibits the use of flammables. Armourshield is actually a rubber and vinyl restorer, but provides an excellent finish and reasonable longevity. Expected period of effective finish is 5 to 9 days. Additionally Armourshield may be sprayed from simple trigger atomizers.

- Slow Drying
- Satin Finish
- Reasonably Durable
- Non Regulated

All information given by Sierra (Aust) Pty Ltd is offered in good faith and is to the best of our knowledge true and accurate. However since conditions of use are beyond our control, all information relevant to dosage is offered without warranty or guarantee and should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any provisions of any Act or Regulation, Federal or State. In particular the information contained herein should not be construed as a representation that the product is suitable for any particular purpose or application.

Sierra (Aust) 17 Delta Street GEEBUNG, Queensland AUSTRALIA
Ph +61 7 3216 5099 Fx +61 7 3216 5199 web: sierrachem.com.au
email: sierra@optusnet.com.au