

SAFETY DATA SHEET

1. Product and Company Identification

Company Name: Sierra Aust Pty Ltd

17 Delta Street, Geebung

- 1 -

Queensland 4034 Ph (07) 3216 5099 Fx (07) 3216 5199 sales@sierrachem.com.au Sierra (07) 3216 5099 Poisons Information Centre 13 11 26

Descaling Fluid Product Name:

Product Code: 9024, 9025

Emergency Contact:

Intended Use: Solution for Removing Scale from Commercial Warewashers

Chemical Nature: Liquid - Mixture

2. Hazards Identification

Hazardous Chemical according to classification by Safe Work Australia

Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail

GHS Classification: Skin Corrosion - Sub category 1B

> Eye Damage Category 1 Corrosive to Metals - Category 1

GHS Signal Word: DANGER

Hazard Statement(s):

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary Statement(s):

Prevention:

P234 Keep only in original container.

P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves / protective clothing / eye protection / face protection

Response:

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P363 Wash contaminated clothing before re-use.

P321 Specific treatment (see First Aid Measures on Safety Data Sheet).

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P390 Absorb spillage to prevent material damage.

Storage:

P405 Store locked up.

P406 Store in corrosive resistant container with a resistant inner liner.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Poisons Schedule (SUSMP): S6 Poison.

Disposal: P501 Dispose of contents/container in accordance with local regulations.

Descaling Fluid SDS

Prepared: 03/09/2024

- 2 - Prepared: 03/09/2024

3. Composition / Information on Ingredients

Ingredients Names and Proportions

Chemical EntityCas NumberProportion(%)Orthophosphoric Acid7664-38-2>40

Surfactant Blend n/a <3

4. First aid Measures

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. For all but the most minor symptoms arrange for patient to be seen by a doctor as soon as possible, either on site or at the nearest hospital.

Skin Contact:

If spilt on large areas of skin or hair, immediately drench with running water and remove clothing. Continue to wash skin and hair with plenty of water (and soap if material is insoluble) until advised to stop by the Poisons Information Centre or a doctor.

Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Ingestion:

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Indication of immediate medical attention and special treatment needed: Treat

symptomatically. Can cause corneal burns.

5. Fire Fighting Measures

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Unsuitable Extinguishing Media:

Water jet.

Hazchem or Emergency Action Code: 2R

Specific hazards arising from the substance or mixture:

Non-combustible material.

Special protective equipment and precautions for fire-fighters:

Decomposes on heating emitting toxic fumes, including those of oxides of phosphorus. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition. Keep containers cool with water spray.

6. Accidental Release Measures

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Neutralise with lime or soda ash. Collect and seal in properly labelled containers or drums for disposal. Wash area down with excess water.

7. Handling and Storage

This material is a Scheduled Poison S6 and must be stored, maintained and used in accordance with the relevant regulations.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols. Keep out of reach of children.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and out of direct sunlight. Protect from freezing. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks. To prevent crystallization of concentrated phosphoric acid solutions, minimum storage temperatures are 21°C for 85% solutions and 4°C for 80% solutions.

8. Exposure Controls and Personal Protection

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Phosphoric acid: 8hr TWA = 1 mg/m³, 15 min STEL = 3 mg/m³

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. If inhalation risk exists: Use with local exhaust ventilation or while wearing suitable mist respirator. Keep containers closed when not in use.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

GOGGLES, FACE SHIELD, GLOVES (Long), APRON, RUBBER BOOTS.

Wear overalls, chemical goggles, face shield, elbow-length impervious gloves, splash apron or equivalent chemical impervious outer garment, and rubber boots. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

If determined by a risk assessment an inhalation risk exists, wear a suitable mist respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Prepared: 03/09/2024

- 4 - Prepared: 03/09/2024

9. Physical and Chemical Properties

Physical state: Clear Liquid Colour: Colourless Odour: Odourless Solubility: Miscible in water. Specific Gravity: 1.38 @15.5°C. Relative Vapour Density (air=1): Not available Flash Point (°C): Not applicable Flammability Limits (%): Not applicable Autoignition Temperature (°C): Not available

pH: ca. 1

10. Stability and Reactivity

Reactivity: Corrodes metals.

Chemical stability: Stable under normal ambient and anticipated storage and handling conditions of

temperature and pressure.

Possibility of hazardous

reactions:

Hazardous polymerisation will not occur. Reacts with metals liberating flammable

hydrogen gas.

Conditions to avoid: Avoid contact with foodstuffs.

Incompatible materials: Phosphoric acid is incompatible with strong oxidising agents, reducing agents,

sulfides, phosphides, cyanides, acetylides, fluorides, silicides, carbides, strong caustic material, alloys, glass, leather, natural rubber, fluorine gas, and arsenic trioxide.

Hazardous decomposition

products:

Oxides of phosphorus.

11. Toxicological Information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and

chemical burns to the gastrointestinal tract.

Eye contact: A severe eye irritant. Corrosive to eyes; contact can cause corneal burns.

Contamination of eyes can result in permanent injury.

Skin contact: Contact with skin will result in severe irritation. Corrosive to skin - may cause skin

burns.

Inhalation: Breathing in mists or aerosols may produce respiratory irritation.

Acute toxicity: No LD50 data available for the product. For the

constituent Phosphoric acid: Oral LD50 (rat): 1250 mg/kg

Chronic effects: Prolonged exposures can cause necrosis of nasal passages and oedema of lungs.

- 5 - Prepared: 03/09/2024

12. Ecological Information

Ecotoxicity Avoid contaminating waterways

13 Disposal Considerations

Disposal methods:

Refer to Waste Management Authority. Dispose of contents/container in accordance with local/regional/national/international regulations.

14. Transport Information

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

UN No: 1805 Transport Hazard Class: 8 Corrosive

Packing Group:

Proper Shipping Name or

Technical Name:

PHOSPHORIC ACID, SOLUTION 2R

Hazchem or Emergency Action

Code:

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1805 Transport Hazard Class: 8 Corrosive

Packing Group: |||

Proper Shipping Name or PHOSPHORIC ACID SOLUTION

Technical Name:

IMDG EMS Fire: F-A IMDG EMS Spill: S-B

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1805 Transport Hazard Class: 8 Corrosive

Packing Group:

Proper Shipping Name or PHOSPHORIC ACID, SOLUTION

Technical Name:

15. Regulatory Information

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS SUBSTANCE.

Classification of the substance or mixture:

Skin Corrosion - Sub-category 1B Eye Damage - Category 1 Corrosive to Metals - Category 1 - 6 - Prepared: 03/09/2024

Hazard Statement(s):

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Poisons Schedule (SUSMP): S6 Poison.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. Other Information

This SDS contains only safety related information. For other information see product literature.

Every endeavor has been made to ensure that the information contained in this publication is reliable and offered in good faith. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. Customers are encouraged to conduct their own tests as end user suitability of the product for particular uses is beyond our control. The information is not intended as an inducement to bargain and no warranty expressed or implied is made as to its accuracy, reliability or completeness. Sierra (Aust) Pty Ltd accepts no liability for loss, injury or damage arising from reliance upon the information contained in this data sheet except in conjunction with the proper use of the product to which it refers. Due care should be taken that the use and disposal of this product is in compliance with appropriate Federal, State and Local Government regulations.