SPECIALISED PRODUCT	- 1 - Revision: 03/0	
1. Product and Cor	npany Identification	
Company Nan Emergency Co	17 Delta Street, Geebung Queensland 4034 Ph (07) 3216 5099 <u>sales@sierrachem.com.au</u> Fx (07) 3216 5199	
Product Name: Product Code: Intended Use: Chemical Nature:	<b>Prepsol</b> 4780 Surface cleaning / preparation Mixture	
2. Hazards Identific	ation	
	ccording to classification by Safe Work Australia fording to the Australian Code for the Transport of Dangerous Goods by Road and Rail	
GHS Classification:	Flammable Liquid Category 2 Aspiration Hazard Category 1 Toxic to reproduction Category 2 Skin Corrosion/Irritation Cat 2 Chronic Aquatic Toxicity Category 2 Specific Target Organ Toxicity (single exposure) Category 3 Specific Target Organ Toxicity (repeated exposure) Category 3	
GHS Signal Word:	DANGER	
Hazard Statement:	5 Highly flammable liquid and vapour, H304 May be fatal if swallowed and enters airways 5 Causes skin irritation H336 May cause drowsiness or dizziness 3 May cause damage to organs through prolonged or repeated exposure 1 Suspected of damaging the unborn child 1 Toxic to aquatic life with long lasting effects	
Precautionary Stateme General:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.	
Preventative:	<ul> <li>P103 Read label before use.</li> <li>P201 Obtain special instructions before use.</li> <li>P202 Do not handle until all safety precautions have been read and understood.</li> <li>P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.</li> <li>P233 Keep container tightly closed.</li> <li>P240 Ground/bond container and receiving equipment.</li> <li>P241 Use explosion proof electrical/ventilation/lighting equipment</li> <li>P242 Use only non-sparking tools</li> <li>P243 Take precautionary measures against static discharge</li> <li>P260 Do not breathe mist/vapours/spray</li> </ul>	

- P260 Do not breathe mist/vapours/spray
- P261 Avoid breathing mist/vapours/spray
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well ventilated area.
- P273 Avoid release to the environment.

**Response:** 

- P280 Wear protective gloves/eye protection/face protection
- P281 Use personal protective equipment as required.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician
- P302+ P352 IF ON SKIN: Wash with plenty of soap and water
  - P303 + P361 + P353 IF ON SKIN (or hair): Take off contaminated clothing and wash before reuse. Rinse skin with water /shower
    - P308 + P313 If exposed or concerned: Get medical advice/attention
    - P304 + P340 If INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

- 2 -

# 3. Composition / Information on Ingredients

## **Ingredients Names and Proportions**

Chemical Entity	Cas Number	Proportion(%)
Solvent naphtha (petroleum)	64742-82-1	100
Light aliphatic		
With components:	440 54 0	40.00
n-Hexane	110-54-3	10 - 30
Ethylbenzene	100-41-4	<10

4. First aid Measures			
In case of eye contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes. If irritation persists transport to nearest medical facility for additional treatment.		
In case of skin contact:	If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available		
If Ingested:	If swallowed, do NOT induce vomiting. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.		
If Inhaled:	Keep victim calm and remove to fresh air if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing.		
Symptoms caused by exposure			
Inhalation:	Breathing of high vapour concentrations may cause central nervous system depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continuous inhalation may result in unconsciousness and death.		
Skin:	May include burning sensation and or a dried/cracked appearance.		
Eyes:	May include burning sensation, redness, swelling and or blurred vision.		
Ingestion:	May include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath and/or fever.		

# Medical attention and special treatment Treat symptomatically

5. Fire Fighting Measures		
Suitable Extinguishing Media:	Foam, water spray or fog, dry chemical powder or carbon dioxide. Do not use water in a jet	
Specific Hazards arising from the Chemical:	Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface of water. Vapour is heavier than air, can spread along ground and distant ignition is possible.	
Special protective equipment for fire fighters:	Wear full protective clothing and self contained breathing apparatus. Hazchem code 3YE	
6. Accidental Release Measures		
Personal Precautions:	Avoid contact with spilled or released material. Shut off leaks, if possible without personal	

risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove

	- 3 -		Revision: 03/09/2024
	all sources of ignition in the surrounding area. Take precautionary measure against static discharge. Ensure electrical continuity by bonding and earthing all equipment.		
Environmental Precautions:	Use appropriate containment to avoid environmental contamination. Prevent from spreading and entering waterway using sand, earth or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Ventilate contaminated area thoroughly.		
Methods of cleanup:	For small spils (<1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely. For larger spills (>1drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Do not flush residues with water. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.		
7. Handling and Storage			
Precautions for safe handling:	Highly flammable product. Avoid breathing vapours. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Flameproof equipment necessary in area where chemical is being used. Vapours may accumulate in low or confined areas.		
Conditions for safe storage:	Store in a well ventilated are heat. Do not store near aero		nition sources and other sources of corrosives.
8. Exposure Controls and F	Personal Protection		
	From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia n-Hexane: 72mg/m <sup>3</sup> (20ppm) TWA (8hr) Shell X55: 450mg/m <sup>3</sup> TWA (8hr)		
Exposure Control Measures:	n-Hexane: 72mg/m <sup>3</sup> (20ppm	n) TWA (8hr)	sion (NOHSC) Worksafe Australia
Exposure Control Measures: Biological Monitoring:	n-Hexane: 72mg/m <sup>3</sup> (20ppm	n) TWA (8hr) 8hr)	sion (NOHSC) Worksafe Australia
	n-Hexane: 72mg/m <sup>3</sup> (20ppm Shell X55: 450mg/m <sup>3</sup> TWA ( No biological limit allocated. Ensure that adequate ventila	n) TWA (8hr) (8hr) ation is provided. Maintair ndards. Avoid generating	
Biological Monitoring:	n-Hexane: 72mg/m <sup>3</sup> (20ppm Shell X55: 450mg/m <sup>3</sup> TWA ( No biological limit allocated. Ensure that adequate ventila recommended exposure sta containers closed when not Wear safety goggles. Use solvent resistant gloves	n) TWA (8hr) (8hr) ation is provided. Maintair Indards. Avoid generating in use.	air concentrations below
Biological Monitoring: Engineering Controls: Individual Protection Measures: Eye and face protection:	n-Hexane: 72mg/m <sup>3</sup> (20ppm Shell X55: 450mg/m <sup>3</sup> TWA ( No biological limit allocated. Ensure that adequate ventila recommended exposure sta containers closed when not Wear safety goggles. Use solvent resistant gloves incidental splashes. If work practices do not main appropriate respiratory prot combination of mask and filt >65°C). respirators should of	n) TWA (8hr) (8hr) ation is provided. Maintair Indards. Avoid generating in use. s, nitrile for longer term pro htain airborne levels below ection equipment. When t er. Select a filter for organ	a air concentrations below and inhaling mists and vapours. Keep otection of PVC and neoprene for v the exposure standard, use using respirators, select an appropriate nic gases and vapours (boiling point
Biological Monitoring: Engineering Controls: Individual Protection Measures: Eye and face protection: Skin protection:	n-Hexane: 72mg/m <sup>3</sup> (20ppm Shell X55: 450mg/m <sup>3</sup> TWA ( No biological limit allocated. Ensure that adequate ventila recommended exposure sta containers closed when not Wear safety goggles. Use solvent resistant gloves incidental splashes. If work practices do not main appropriate respiratory prot combination of mask and filt	n) TWA (8hr) (8hr) ation is provided. Maintair Indards. Avoid generating in use. s, nitrile for longer term pro htain airborne levels below ection equipment. When t er. Select a filter for organ	a air concentrations below and inhaling mists and vapours. Keep otection of PVC and neoprene for v the exposure standard, use using respirators, select an appropriate nic gases and vapours (boiling point
Biological Monitoring: Engineering Controls: Individual Protection Measures: Eye and face protection: Skin protection: Respiratory protection:	n-Hexane: 72mg/m <sup>3</sup> (20ppm Shell X55: 450mg/m <sup>3</sup> TWA ( No biological limit allocated. Ensure that adequate ventila recommended exposure stat containers closed when not Wear safety goggles. Use solvent resistant gloves incidental splashes. If work practices do not main appropriate respiratory prot combination of mask and filt >65°C). respirators should o state/territory authority. Not applicable.	n) TWA (8hr) (8hr) ation is provided. Maintair Indards. Avoid generating in use. s, nitrile for longer term pro htain airborne levels below ection equipment. When t er. Select a filter for organ	a air concentrations below and inhaling mists and vapours. Keep otection of PVC and neoprene for v the exposure standard, use using respirators, select an appropriate nic gases and vapours (boiling point

Upper/lower flammability: 1.0 - 7.5

or explosive limits (%)

Typical 34.5

Vapour pressure:

(kPa@20°C)

Reactivity:	Stable under normal conditions of use
Chemical Stability:	Stable under normal conditions of use
Possible Hazardous reactions:	Stable under normal conditions of use
Conditions to avoid:	Avoid heat, sparks, open flames and other ignition sources
Incompatible materials:	Strong oxidizing agents.
Hazardous Decomposition produ	icts: Thermal decomposition is highly dependent on condition

Hazardous Decomposition products: Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids, gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

# 11. Toxicological Information

Acute toxicity:	Expected to be of low toxicity - LD50 Oral (rat) > 2000 mg/kg	
Skin corrosion/irritation:	Irritating to skin. Prolonged contact may cause defatting of skin which can lead to dermatitis.	
Serious eye damage/irritation:	Expected to be non-irritating to eyes.	
Respiratory or skin sensitisation:	Not expected to be a sensitiser.	
Germ cell mutagenicity:	Not mutagenic.	
Carcinogenicity:	Not expected to be carcinogenic.	
Reproductive toxicity:	Causes foetus toxicity in animals at doses which are maternally toxic. Affects reproductive system in animals at doses which produces other toxic affects (n-Hexane).	
Specific Target Organ Toxicity (STOT) – single exposure:	Not expected to be a respiratory irritant.	
Specific Target Organ Toxicity (STOT) – repeated exposure:	Central nervous system: repeated exposure affects the nervous system.	
Aspiration hazard:	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.	

# **12. Ecological Information**

## Ecotoxicity

## Acute toxicity:

Fish –	Expected to be toxic: 1 < LC/EC/IC50 <= 10mg/I
Aquatic invertebrate –	Expected to be toxic: 1 < LC/EC/IC50 <= 10mg/I
Algae –	Expected to be toxic: 1 < LC/EC/IC50 <= 10mg/I
Microorganisms –	Expected to be harmful: 1 < LC/EC/IC50 <= 10mg/l

Chronic toxicity:

Fish –	Data not available
Aquatic invertebrate –	Data not available
Algae –	Data not available

|--|

#### Persistence and degradability

Readily biodegradable. Oxidises by photo-chemical reactions in air.

#### **Bioaccumulative potential**

Has the potential to bioaccumulate.

#### Mobility in soil

Floats on water. Absorbs on soil.

#### **13 Disposal Considerations**

Ensure waste disposal conforms to local waste disposal regulations.

#### 14. Transport Information

UN number:	1268
Proper shipping name:	Petroleum Distillates, N.O.S. (solvent naphtha)
Australian Dangerous Goods class:	3
Australian Dangerous Goods packing group:	П
Hazchem code:	3YE

15. Regu	latory In	formation
----------	-----------	-----------

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:	5		
Australian Inventory of Chemical Substances (AICS):	Listed		
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76):	14		

## 16. Other Information

#### This SDS contains only safety related information. For other information see product literature.

Every endeavor has been made to ensure that the information contained in this publication is reliable and offered in good faith. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. Customers are encouraged to conduct their own tests as end user suitability of the product for particular uses is beyond our control. The information is not intended as an inducement to bargain and no warranty expressed or implied is made as to its accuracy, reliability or completeness. Sierra (Aust) Pty Ltd accepts no liability for loss, injury or damage arising from reliance upon the information contained in this data sheet except in conjunction with the proper use of the product to which it refers. Due care should be taken that the use and disposal of this product is in compliance with appropriate Federal, State and Local Government regulations.